ï~.

FORM PTO-892 (REV. 2-92)							TMENT OF CON		D8		GROUP ART UNIT ATTAC			3				
NOTICE OF REFERENCES CITED APPLICANT(S) P // g C												1/9 (2)	1111 PAPER S NUMBER 3					
E										U.S. PATE	ENT DOCU	MENTS	-					
·	L		D	ocı	JME	ŠτN	ю.	_	DATE	_/	CLA		SUB- LASS	APPROP	ATE IF			
L	Δ	3	5	0	8	9	5	5	4/1970	5/in 5/i	50	38 1	OF					
L	В	3	4	1	9	3	6	3	12/1968	<u>5/i</u>	50	18/	104					
L	C	L	L	_	<u> </u>		<u> </u>					_						
_	P	L	_	_	L							\perp						
F	Ε_		-	-							-							
-	F	H	H	H		Н			· · · · · · · · · · · · · · · · · · ·	<u></u>			-					
L	G H			H		Н							-			·		
			-	H							-		+					
-]	H		Н	-	H	Н		:				+	+				
┝	ĸ												╁			····		
		نـــا		لـــا					F	DREIGN PA	TENT DO	CUMENTS	<u> </u>					
·	Ì	DOCUMENT NO. DATE COU					NTRY	NAME		CLASS	SUB- CLASS		PP.					
	L																	
	м						_	\bot										
_	N	_		\downarrow	_	4	_	_							ļ			
	0	\dashv	_	\downarrow		4						<u></u>						
	Р	_	_	4	_	\dashv	4	4					`		<u> </u>			
_	a	_	J	_				<u></u>	EE DENOES A									
_	1	OTHER REFERENCES (Including Author, Title, Date, Pertinent Pages, Etc.) The Ext Effect of Compositional Tailoring on the Thermon																
*	R	J.	Me Un	. C							1 -			144	4	olid		
		h	Expansion and Tribological Properties of PS 300; A solid bubricant Composite Coating, Dellacorte + posses, 1996															
	S	7	<u> </u>	<u>· ·</u>	<u></u>	<u>V</u> 1.			71170-1.1		,,,,,,	10,0,7,1	, , , , , , , , , , , , , , , , , , , 	· R	WASTE O		7774	
S.	-	1	ri	b	o lo	9/	ca	1	Evalua	tion o	FPS	300: A	Neu	Chi	rome	Okio	le	
*		B	a	se	ď	J_	20	أرط	1 Jubric	art	Coat		,	7		A/20.	7	
	U	From 25 to 650°C																
EX	MIN	ER	_						DATE		<u>a</u>			·				
	("	<u></u>)	9	ر -			15/	12/19	1		_		•			
						• /	A c (S	opy ee M	of this refere lanual of Pate	nce is not	being fur	nished with the	is offici 707.05	action).			